

二代變形鎢鋼立銑刀 Exchangeable Head Endmill 2

刀具推薦表詳見 P.54
Selection of Endmill P.54

X-WDEX



抗震鎢鋼刀桿 (內冷孔)
Solid Carbide Shank (Internal Coolant Hole)



型號 Type No.	D1 柄徑 Shank Dia.	L1 全長 O.A.L.	M 螺牙 Thread Size
X-WDEX-080060	8.0	60	M 5 -3P
X-WDEX-080075	8.0	75	M 5 -3P
X-WDEX-080100	8.0	100	M 5 -3P
X-WDEX-100060	10.0	60	M 7 -3P
X-WDEX-100075	10.0	75	M 7 -3P
X-WDEX-100100	10.0	100	M 7 -3P
X-WDEX-100150	10.0	150	M 7 -3P
X-WDEX-120060	12.0	60	M 8 -3P
X-WDEX-120080	12.0	80	M 8 -3P
X-WDEX-120100	12.0	100	M 8 -3P
X-WDEX-120150	12.0	150	M 8 -3P
X-WDEX-160060	16.0	60	M10 -3P
X-WDEX-160080	16.0	80	M10 -3P
X-WDEX-160100	16.0	100	M10 -3P
X-WDEX-160150	16.0	150	M10 -3P
X-WDEX-160200	16.0	200	M10 -3P
X-WDEX-200060	20.0	60	M12 -3P
X-WDEX-200080	20.0	80	M12 -3P
X-WDEX-200100	20.0	100	M12 -3P
X-WDEX-200150	20.0	150	M12 -3P
X-WDEX-200200	20.0	200	M12 -3P
X-WDEX-200250	20.0	250	M12 -3P
X-WDEX-200300	20.0	300	M12 -3P
X-WDEX-250100	25.0	100	M16 -3P
X-WDEX-250150	25.0	150	M16 -3P
X-WDEX-250200	25.0	200	M16 -3P
X-WDEX-250250	25.0	250	M16 -3P
X-WDEX-250300	25.0	300	M16 -3P
X-WDEX-320100	32.0	100	M20 -3P
X-WDEX-320150	32.0	150	M20 -3P
X-WDEX-320200	32.0	200	M20 -3P
X-WDEX-320250	32.0	250	M20 -3P
X-WDEX-320300	32.0	300	M20 -3P

X-WHEX



抗震鎢鋼刀桿 (內冷孔)
Solid Carbide Shank (Internal Coolant Hole)



型號 Type No.	D2 頸徑 Neck Dia.	L1 全長 O.A.L.	L2 有效長 Effective Length	D1 柄徑 Shank Dia.	M 螺牙 Thread Size
X-WHEX-080060	7.8	60	15	8.0	M 5 -3P
X-WHEX-080075	7.8	75	20	8.0	M 5 -3P
X-WHEX-080100	7.8	100	20	8.0	M 5 -3P
X-WHEX-100060	9.8	60	15	10.0	M 7 -3P
X-WHEX-100075	9.8	75	20	10.0	M 7 -3P
X-WHEX-100100	9.8	100	20	10.0	M 7 -3P
X-WHEX-100150	9.8	150	40	10.0	M 7 -3P
X-WHEX-120060	11.7	60	15	12.0	M 8 -3P
X-WHEX-120080	11.7	80	20	12.0	M 8 -3P
X-WHEX-120100	11.7	100	60	12.0	M 8 -3P
X-WHEX-120150	11.7	150	90	12.0	M 8 -3P
X-WHEX-160060	15.6	60	15	16.0	M10 -3P
X-WHEX-160080	15.6	80	30	16.0	M10 -3P
X-WHEX-160100	15.6	100	60	16.0	M10 -3P
X-WHEX-160150	15.6	150	90	16.0	M10 -3P
X-WHEX-160200	15.6	200	120	16.0	M10 -3P
X-WHEX-200060	19.5	60	20	20.0	M12 -3P
X-WHEX-200080	19.5	80	40	20.0	M12 -3P
X-WHEX-200100	19.5	100	60	20.0	M12 -3P
X-WHEX-200150	19.5	150	90	20.0	M12 -3P
X-WHEX-200200	19.5	200	120	20.0	M12 -3P
X-WHEX-200250	19.5	250	150	20.0	M12 -3P
X-WHEX-200300	19.5	300	180	20.0	M12 -3P
X-WHEX-250100	24.4	100	50	25.0	M16 -3P
X-WHEX-250150	24.4	150	90	25.0	M16 -3P
X-WHEX-250200	24.4	200	120	25.0	M16 -3P
X-WHEX-250250	24.4	250	150	25.0	M16 -3P
X-WHEX-250300	24.4	300	180	25.0	M16 -3P
X-WHEX-320100	31.2	100	50	32.0	M20 -3P
X-WHEX-320150	31.2	150	90	32.0	M20 -3P
X-WHEX-320200	31.2	200	120	32.0	M20 -3P
X-WHEX-320250	31.2	250	150	32.0	M20 -3P
X-WHEX-320300	31.2	300	180	32.0	M20 -3P

X-WFEX



抗震鎢鋼刀桿 (內冷孔)
Solid Carbide Shank (Internal Coolant Hole)



型號 Type No.	D2 頸徑 Neck Dia.	L1 全長 O.A.L.	L2 有效長 Effective Length	L3 斜頭長 T.A.L.	D1 柄徑 Shank Dia.	M 螺牙 Thread Size	α 斜角 Taper Angle
X-WFEX-120100	9.8	100	2	44	12.0	M 7 -3P	1.5
X-WFEX-120150	9.8	150	2	65	12.0	M 7 -3P	1.0
X-WFEX-160100	11.7	100	3	50	16.0	M 8 -3P	2.0
X-WFEX-160150	11.7	150	3	85	16.0	M 8 -3P	1.5
X-WFEX-160200	11.7	200	3	126	16.0	M 8 -3P	1.0
X-WFEX-200100	15.6	100	4	50	20.0	M10 -3P	2.0
X-WFEX-200150	15.6	150	4	88	20.0	M10 -3P	1.5
X-WFEX-200200	15.6	200	4	130	20.0	M10 -3P	1.0
X-WFEX-250200	19.5	200	6	111	25.0	M12 -3P	1.5
X-WFEX-250300	19.5	300	6	164	25.0	M12 -3P	1.0
X-WFEX-320300	24.4	300	8	153	32.0	M16 -3P	1.5