



### 3 X D / POWER MAX DRILL STUB / HIGH SPEED MACHINING

- Suitable for high speed cutting with newly developed raw-material and new coating.

## PF503 ...series



EDP. No.	Dia.			L <sub>1</sub>	L <sub>2</sub>	D <sub>2</sub>	STOCK
	mm	fraction	inch				
PF50305558	5.558	7/32	.2188	30	66	6	•
PF503056	5.6	-	.2205				•
PF503057	5.7	-	.2244				•
PF503058	5.8	-	.2283				•
PF503059	5.9	-	.2323				•
PF50305953	5.953	15/64	.2344				•
PF503060	6.0	-	.2362				•
PF503061	6.1	-	.2402				•
PF503062	6.2	-	.2441				•
PF503063	6.3	-	.24				•
PF5030635	6.350	1/4	80	34	74	7	•
PF503064	6.4	-	.2500				•
PF503065	6.5	-	.2520				•
PF503066	6.6	-	.2559				•
PF503067	6.7	-	.2598				•
PF50306747	6.747	17/64	.2638				•
PF503068	6.8	-	.2656				•
PF503069	6.9	-	.2677				•
PF503070	7.0	-	.2717				•
PF503071	7.1	-	.2756				•
PF50307145	7.145	9/32	.2795	40	79	8	•
PF503072	7.2	-	.2813				•
PF503073	7.3	-	.2835				•
PF503074	7.4	-	.2874				•
PF503075	7.5	-	.2913				•
PF50307541	7.541	19/64	.2953				•
PF503076	7.6	-	.2969				•
PF503077	7.7	-	.2992				•
PF503078	7.8	-	.3031				•
PF503079	7.9	-	.3071				•
PF50307938	7.938	5/16	.3110	43	84	9	•
PF503080	8.0	-	.3125				•
PF503081	8.1	-	.3150				•
PF503082	8.2	-	.3189				•
PF503083	8.3	-	.3228				•
PF50308334	8.334	21/64	.3268				•
PF503084	8.4	-	.3281				•
PF503085	8.5	-	.3307				•
PF503086	8.6	-	.3346				•
PF503087	8.7	-	.3386				•
PF50308733	8.733	-	.3425	•			
PF503088	8.8	-	.3438	•			