



5 X D / POWER MAX DRILL MEDIUM / HIGH SPEED MACHINING

- Suitable for high speed cutting with newly developed raw-material and new coating.

PF505 ...series



EDP. No.	Dia.			L ₁	L ₂	D ₂	STOCK
	mm	fraction	inch				
PF505030	3.0	-	.1193	25		3	•
PF505031	3.1	-	.1233				•
PF50503175	3.175	1/8	.1250		60		•
PF505032	3.2	-	.1260	27			•
PF50503264	3.264	#30	.1285				•
PF505033	3.3	-	.1299				•
PF505034	3.4	-	.1339				•
PF505035	3.5	-	.1378			4	•
PF50503572	3.572	9/64	.1406	30	65		•
PF505036	3.6	-	.1417				•
PF505037	3.7	-	.1457				•
PF505038	3.8	-	.1496				•
PF505039	3.9	-	.1535	33	71		•
PF50504039	4.039	#21	.1575				•
PF505040	4.0	-	.1590				•
PF505041	4.1	-	.1614	33			•
PF505042	4.2	-	.1654				•
PF505043	4.3	-	.1693				•
PF505044	4.4	-	.1732				•
PF505045	4.5	-	.1772	36	71	5	•
PF505046	4.6	-	.1811				•
PF505047	4.7	-	.1850				•
PF50504763	4.763	3/16	.1875				•
PF505048	4.8	-	.1890				•
PF505049	4.9	-	.1929	39			•
PF505050	5.0	-	.1969				•
PF505051	5.1	-	.2008				•
PF50505159	5.159	13/64	.2031	39			•
PF505052	5.2	-	.2047				•
PF505053	5.3	-	.2087				•
PF505054	5.4	-	.2126				•
PF505055	5.5	-	.2165				•
PF50505558	5.558	7/32	.2188		83	6	•
PF505056	5.6	-	.2205				•
PF505057	5.7	-	.2244	43			•
PF505058	5.8	-	.2283				•
PF505059	5.9	-	.2323				•
PF50505953	5.953	15/64	.2344				•
PF505060	6.0	-	.2362				•
PF505061	6.1	-	.2402				•
PF505062	6.2	-	.2441	47	87	7	•
PF505063	6.3	-	.2480				•