



### 5 X D / POWER MAX DRILL MEDIUM / HIGH SPEED MACHINING

- Suitable for high speed cutting with newly developed raw-material and new coating.

## PF505 ...series



EDP. No.	Dia.			L <sub>1</sub>	L <sub>2</sub>	D <sub>2</sub>	STOCK
	mm	fraction	inch				
PF5050635	6.350	1/4	.2500	47	87	7	•
PF505064	6.4	-	.2520				•
PF505065	6.5	-	.2559				•
PF505066	6.6	-	.2598				•
PF505067	6.7	-	.2638				•
PF50506747	6.747	17/64	.2656				•
PF505068	6.8	-	.2677				•
PF505069	6.9	-	.2717				•
PF505070	7.0	-	.2756				•
PF505071	7.1	-	.2795				•
PF50507145	7.145	9/32	.2813	52	92	8	•
PF505072	7.2	-	.2835				•
PF505073	7.3	-	.2874				•
PF505074	7.4	-	.2913				•
PF505075	7.5	-	.2953				•
PF50507541	7.541	19/64	.2969				•
PF505076	7.6	-	.2992				•
PF505077	7.7	-	.3031				•
PF505078	7.8	-	.3071				•
PF505079	7.9	-	.3110				•
PF50507938	7.938	5/16	.3125	56	96	9	•
PF505080	8.0	-	.3150				•
PF505081	8.1	-	.3189				•
PF505082	8.2	-	.3228				•
PF505083	8.3	-	.3268				•
PF50508334	8.334	21/64	.3281				•
PF505084	8.4	-	.3307				•
PF505085	8.5	-	.3346				•
PF505086	8.6	-	.3386				•
PF505087	8.7	-	.3325				•
PF50508733	8.733	11/32	.3338	62	105	10	•
PF505088	8.8	-	.3465				•
PF505089	8.9	-	.3504				•
PF505090	9.0	-	.3543				•
PF505091	9.1	-	.3583				•
PF50509129	9.129	23/64	.3594				•
PF505092	9.2	-	.3622				•
PF505093	9.3	-	.3661				•
PF505094	9.4	-	.3701				•
PF505095	9.5	-	.3740				•
PF50509525	9.525	3/8	.3750	•			
PF505096	9.6	-	.3780	•			