



### 3 X D / POWER MAX DRILL STUB / INTERNAL COOLANT

- Suitable for high speed cutting with newly developed raw-material and new coating.

## SF503 ...series



EDP. No.	Dia.			L <sub>1</sub>	L <sub>2</sub>	D <sub>2</sub>	STOCK		
	mm	fraction	inch						
SF503030	3.0	-	.1193	18	60	3	•		
SF503031	3.1	-	.1233	20		4	•		
SF50303175	3.175	-	.1250				•		
SF503032	3.2	-	.1260				•		
SF50303246	3.264	-	.1285				•		
SF503033	3.3	-	.1299				•		
SF503034	3.4	-	.1339	22			•		
SF503035	3.5	-	.1378				•		
SF50303572	3.572	-	.1406				•		
SF503036	3.6	-	.1417				•		
SF503037	3.7	-	.1457				•		
SF503038	3.8	-	.1496	24			•		
SF503039	3.9	-	.1535				•		
SF503040	4.0	-	.1575				•		
SF50304039	4.039	-	.1590		24	62	•		
SF503041	4.1	-	.1614				•		
SF503042	4.2	-	.1654	26	5		•		
SF503043	4.3	-	.1693				•		
SF503044	4.4	-	.1732				•		
SF503045	4.5	-	.1772				•		
SF503046	4.6	-	.1811				•		
SF503047	4.7	-	.1850				•		
SF50304763	4.763	-	.1875				•		
SF503048	4.8	-	.1890				•		
SF503049	4.9	-	.1929				•		
SF503050	5.0	-	.1969				28	6	•
SF503051	5.1	-	.2008						•
SF50305159	5.159	-	.2031						•
SF503052	5.2	-	.2047	•					
SF503053	5.3	-	.2087	•					
SF503054	5.4	-	.2126	•					
SF503055	5.5	-	.2165	•					
SF50305558	5.558	-	.2188	30	•				
SF503056	5.6	-	.2205		•				
SF503057	5.7	-	.2244		•				
SF503058	5.8	-	.2283		•				
SF503059	5.9	-	.2323		•				
SF50305953	5.953	-	.2344		•				
SF503060	6.0	-	.2362		•				
SF503061	6.1	-	.2402	34	74	7	•		
SF503062	6.2	-	.2441				•		
SF503063	6.3	-	.2480				•		