



3 X D / POWER MAX DRILL STUB / INTERNAL COOLANT

- Suitable for high speed cutting with newly developed raw-material and new coating.

SF503 ...series



EDP. No.	Dia.			L ₁	L ₂	D ₂	STOCK			
	mm	fraction	inch							
SF5030635	6.350	-	.2500	34	74	7	•			
SF503064	6.4	-	.2520				•			
SF503065	6.5	-	.2559				•			
SF503066	6.6	-	.2598				•			
SF503067	6.7	-	.2638	37			•			
SF50306747	6.747	-	.2656				•			
SF503068	6.8	-	.2677				•			
SF503069	6.9	-	.2717				•			
SF503070	7.0	-	.2756				•			
SF503071	7.1	-	.2795				•			
SF50307145	7.145	-	.2813	40			79	8	•	
SF503072	7.2	-	.2835						•	
SF503073	7.3	-	.2874						•	
SF503074	7.4	-	.2913						•	
SF503075	7.5	-	.2953		•					
SF50307541	7.541	-	.2969		•					
SF503076	7.6	-	.2992		•					
SF503077	7.7	-	.3031		•					
SF503078	7.8	-	.3071		•					
SF503079	7.9	-	.3110		•					
SF50307938	7.938	-	.3125		•					
SF503080	8.0	-	.3150		•					
SF503081	8.1	-	.3189		43	84			9	•
SF503082	8.2	-	.3228							•
SF503083	8.3	-	.3268	•						
SF50308334	8.334	-	.3281	•						
SF503084	8.4	-	.3307	•						
SF503085	8.5	-	.3346	•						
SF503086	8.6	-	.3386	•						
SF503087	8.7	-	.3325	•						
SF50308733	8.733	-	.3338	•						
SF503088	8.8	-	.3465	•						
SF503089	8.9	-	.3504	•						
SF503090	9.0	-	.3543	•						
SF503091	9.1	-	.3583	47			89	10		•
SF50309129	9.129	-	.3594							•
SF503092	9.2	-	.3622		•					
SF503093	9.3	-	.3661		•					
SF503094	9.4	-	.3701		•					
SF503095	9.5	-	.3740		•					
SF50309525	9.525	-	.3750		•					
SF503096	9.6	-	.3780		•					